

MONARCH 2.0 MP

AM-S2016-VM

**Full HD 2.0 Megapixel
VARI FOCAL DOME IP CAMERA**

Superior Engineering Design & Sensational Image Quality

AM-S2016-VM

Full HD 2.0 Megapixel VARI FOCAL DOME IP CAMERA

Features :

- 1/2.8" CMOS Exmor Image Sensor with 2.0 Mega Pixel
- Full HD Resolution with 1920(H) x 1080(V)
- True & Soft Day/Night for all 24/7 Surveillance mode
- Triplex Compression Streaming H.264, MPEG4, MJPEG for Network, Record, Image
- Selectable Three or Dual or Single Streaming Combination For simultaneously Operation
- Powered through Power over Ethernet(PoE) with IEEE 802.3af Standard
- Compliant with ONVIF 2.0 on May, 2012
- "Common Gateway Information API for 3rd party intrigration CMS/VAS/NVR "
- Low illumination 0.3Lux(Color), 0.03Lux(B/W)
- Wide Very Focal 3.3 to 10MM Mega Pixel Auto IRIS Lens
- Noise Reduction by SNF & TNF
- Supported Local Storage by Micro SD(up to 32G), USB Slot for Wireless Application(Future Expansion Optional)
- Compatible with AVTRON Free Software Live up to 36CH with 16CH Playback Support
- Built in Multicast Streaming by that Large number of User can log on with Sensible Video Quality
- Wide Range Supported Network Protocol TCP/IP, UDP, RTP, RTSP, NTP, HTTP, DHCP, FTP, SMTP, DNS, DDNS
- Flexible & Selectable Video Stream Control by VBR & CBR
- Support Bi-Directional(Two-Way) Audio Communication (G.711/AAC)
- OSD Menu Control BY Confrigration Menu
- Support Mirror Function with Horizontal, Vertical Direction
- Adjustable Exposure Mode Auto/Flicker/ Manual, Sense-Up
- Support Email Notification, FTP Upload, Composite Video Output
- Easy, Fast & User Friendly GUI CMS & Network Discovery BY UPnP
- Multi User Support with Software Access Level Control with Password Protection
- 3rd party System intrigration by RS485/Sensor/Relay
- 8 Zone Arbitrary rect.Areas Motion Detection, BLC, Privacy Masking, Camera ID & etc
- Dual Power Support by 12V DC & POE
- 3 Axis Bracket, ABS Plastic with illustration Dome Cover



Specifications :

Model No.	AM-S2016-VM
Camera Specification	
Sensor Type	1/2.8" pixel CMOS ExMor Sensor
Effective Pixels	Effective Max Pixel 2.35M with 1936(H) x 1217(V)
Lux Level(illumination)	0.3Lux @ Color, 0.03 Lux @ B/W @ F1.3
Shutter Speed Control	AUTO 1/30s-1/12,000s
Gain Control(AGC)	Low/MID/HIGH/HIGH Plus
Lens	3.3 ~ 10mm DC Auto IRIS
White Balance	Auto/ATC/Fixed/Manual
On Screen Display	
Day/Night	Auto / Color / BW
Digital Noise Reduction	Off/SNF/TNF/SNF+TNF
Sens-Up	up to 8X
Back Light Compensation(BLC)	Off/Low/Mid/High
Camera ID Name	On/Off
Privacy Masking	On/Off (max.10 areas, 6 colors)
OSD Menu Control	Yes
Mirror	Off/H/V/H+V
Motion Detection	8 subjective rect. Areas
Image Control	Brightness, Contrast, Sharpness, Saturation
Compression/Video/Audio	
Video Compression	H.264 / MPEG4 / MJPEG
Video Resolution	Max. 1920x1080, 1280x1024, 1280x960, 1600x900, 1024x760, 1280x720, 800x600, 720x480, 640x480
Record & Live Frame rate	Selectable 1 ~ 30fps
Rate control	VBR/CBR, I-Frame interval
Bit Rate	32Kbps ~ 8MBPS
Streaming	Single or dual or Triple configured by H.264, MPEG4 and MJPEG
Video output	Composite by RCA Socket(Analog) / RJ-45

Specifications :

Signal System	PAL/NTSC/Analog RGB Selectable
Audio Compression	G.711u(64kbps), AAC(128kbps)
Audio Connection	Line in / Line out (Stereo JACK)
Communication	Bi-directional
Software Intrigration	
Onvif	YES, V2.0
CMS Record	CAMMANAGER 36CH Record @ up to 2.0 M Resolution
CMS Playback	16CH Playback Support
3rd Party VMS/NVR /CMS	BY Onvif V2.0 / CGI
Event Trigger	BY Motion detection, Alarm Port
Event Handing	On-screen alerts/Mail/FTP/Configurable alert sound/Record
Event Recording	Pre-record (3sec.)/Post-record (30sec.)
FTP Upload	YES
EMAIL Notifiacion	YES
Memory & Storage	
DDR RAM	256MB
FLASH RAM	64MB
Storage	Micro SD Slot(32GB Max.)
Network	
Connection	RJ-45 Ethernet
Protocol	TCP/IP, UDP, RTP, RTSP, NTP, HTTP, DHCP, FTP, SMTP, DNS, DDNS
Streaming	Unicast, Multicast
Access control	Access levels with password protection
DDNS	Yes(dyndns)
Network discovery	UPnP
LAN Connectivity	10/100 Based-T
Interface	
RS-485	Yes
Sensor	1 x Sensor Input
Alarm	1x Alarm Output(Relay)
General	

Specifications :

Power Supply	PoE, IEEE802.3af & DC 12V
Power Consumption	<420 mA
Operating Temperature	-10°C ~ + 50°C
Operating Humidity	30% ~ 90% RH
Mechanical	
Weight (g)	530g Approx.
Mechanism	3 Axis, Metal Bracket
Dome	Optical Corrected Dome Cover

* Product specifications and appearance may be changed without prior notice due to improvements.



Scan with your
Smart phone for
more information
www.avtrontech.com

The AVTRON logo consists of a stylized blue 'V' symbol followed by the word 'AVTRON' in a bold, black, sans-serif font.

www.avtrontech.com | info@avtrontech.com