


High Resolution Dome Camera with OSD



Main Features

- ⇒ 1/3" Sony CCD
- ⇒ 650 TVL High Resolution Camera
- ⇒ 0.005lux@F1.2
- ⇒ 3.6 mm Fixed Lens
- ⇒ AGC, AWB, BLC, Mirror, Privacy Masking and Motion Detection
- ⇒ CE, FCC and RoHS Certified



| Feature | Specification |
|-------------------------|---|
| Image Sensor | 1/3" Sony CCD |
| Pixels | PAL:752Hx582V, NTSC:768Hx494V |
| Resolution | 650 TVL |
| Min. Illumination | 0.005lux@F1.2 |
| S/N Ratio | more than 48dB |
| Electronic Shutter | 1/50(1/60) - 1/100000 Sec |
| Flickerless Mode | ON/OFF |
| Lens | 3.6 mm |
| Gamma Correction | 0.45 |
| White Balance (AWB) | Auto |
| Gain Control (AGC) | ON/OFF Selectable |
| Back Light Compensation | ON/OFF Selectable |
| Sync | Internal |
| Video Output | 1.0 Vp-p/75 ohm |
| Special Functions | OSD, Camera ID, Camera Title, Mirror, Privacy Masking=7, Motion Detection=4 |
| Power Supply | DC 12V ± 5% |
| Power Consumption | <4W |
| Dimensions | 100 x 65mm |
| Weight | 230g |
| Operating Temperature | -10~50 °C |
| Certifications | CE, FCC, RoHs |