


High Resolution Vandal VF IR Dome Camera with OSD- 30 Mtr.



Main Features

- ⇒ 1/3" Sony Super HAD II
- ⇒ 650 TVL High Resolution Camera
- ⇒ 0 lux @ F1.2 (IR ON)
- ⇒ 4~9 mm Vari-Focal Auto Iris Lens
- ⇒ IR Range of 30 Mtrs with 30 Blue LEDs
- ⇒ AGC, AES, BLC, HLC, Mirror, Privacy Masking and
- ⇒ Sens Up, 2D-DNR, 3D-DNR, LSC, DIS and Eclipse
- ⇒ CE, FCC and RoHS Certified



| Feature | Specification |
|-------------------------|---|
| Image Sensor | 1/3" Sony Super HAD II |
| Pixels | PAL:752Hx582V, NTSC:768Hx494V |
| Resolution | 650 TVL |
| Min. Illumination | 0 lux @F1.2 |
| S/N Ratio | more than 48dB |
| Electronic Shutter | 1/50(1/60) - 1/100000 Sec |
| Flickerless Mode | ON/OFF |
| Lens | 4~9 mm Vari-Focal Auto Iris Lens |
| Focus Mode | Manual |
| Gamma Correction | 0.45 |
| White Balance (AWB) | Auto |
| Gain Control (AGC) | Auto |
| Back Light Compensation | ON/OFF Selectable |
| High Light Compensation | Yes |
| IR | 30 Blue LEDs, Upto 30 Mtrs |
| WDR | No |
| Sync | Internal/External Line Lock |
| Video Output | 1.0 Vp-p/75 ohm |
| Special Functions | OSD, Camera ID, Camera Title, Mirror, Privacy Masking=7, Motion Detection=4, Sens-Up(Low Shutter)=x256, 2D-DNR, 3D-DNR, LSC, DIS, ECLIPSE |
| Power Supply | DC 12V ± 5% |
| Power Consumption | <4W |
| Dimensions | 100 x 150mm |
| Weight | 900g |
| Operating Temperature | -10~50 °C |
| Certifications | CE, FCC, RoHs |