

HD 720P Mini Dome IP Camera



Main Features

- ⇒ 1/2.7" Progressive CMOS Image Sensor
- ⇒ Full HD 1080p @15fps/HD 720p real-time at dual streaming
- ⇒ H.264 and MJPEG compression
- ⇒ Power over Ethernet (802.3af)
- ⇒ Max 32GB SD Card for Local Storage(optional)
- ⇒ One Way Audio
- ⇒ 3D-DNR, WDR, Digital Zoom, Privacy Masks, Motion Detection
- ⇒ Built-in Web server, CMS & MSS

Feature	Specification
Image Sensor	1/2.7" Progressive CMOS
Minimum Illumination	0.1 lux @ F 1.5
Shutter Speed	1~ 1/10000 sec.
White Balance	Auto / Manual
Lens	4.0 mm
Video Compression	H.264/MJPEG
Video Streaming	Dual Streams 1080p (15 / 25 fps) + D1 (30 / 25 fps), Quad Streams H.264 * 4 / H.264 * 3 + MJPEG
Resolution	H.264- Full HD 1080P/SXGA/HD 720P/XGA/SVGA/D1/VGA/CIF, MJPEG- Full HD 1080P/SXGA/HD 720P/XGA/SVGA/D1/VGA/CIF
Frame Rate	HD 15fps, Full HD 30 fps
Digital Zoom	Support
Motion detection	On/Off
Privacy Mask	On/Off
Privacy Mask Type	Color
Tampering Alarm	On/Off
Audio Input	One Way Audio: Mic in
Audio Compression	G.711 / G.726
Event Notification	HTTP, FTP, SMTP
Multiple Languages	English, French, German, Italian, Korean, Simplified Chinese, Russian
Interface	10/100Mbps Ethernet (RJ-45)
Protocol	IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS
Password Levels	User and Administrator
Security	HTTPS, IP Filter, IEEE 802.1X
Internet Browser	Internet Explorer (6.0+), Chrome, Firefox, Safari
User Account	20
Micro SD	microSDHC 32GB support

Feature	Specification
Operating Temperature	-10° ~ 50°C (14° ~ 122° F)
Humidity	10% to 90%, No Condensation
Power Source	PoE
Power Consumption	3.5 W
Weatherproof Standard	Rugged Camera- IP66
Regulatory	CE, FCC, RoHS Compliant
Dimension	Ø 110.2 x 47.7 mm (Ø 4.3 x 1.9 in.)
Weight	180 g (0.40 lbs)