

# DH-DMS26V1

## High Resolution Vari-Focal Dome Camera with OSD



### Main Features

- 1/3" Sony CCD
- 520 TVL High Resolution Camera
- 0.3 Lux @ F1.2
- 4~9 mm Vari-Focal Manual Iris Lens
- D-WDR/2DNR/DPC/Lens Shading/De-Moire Suppress/  
Motion Detection/Privacy Region Shielded
- AGC, AWB and BLC
- CE, FCC Certified



| Feature                 | Specification                         |
|-------------------------|---------------------------------------|
| Image Sensor            | 1/3" Sony CCD                         |
| Pixels                  | PAL:ICX633BK/NTSC:ICX632BK            |
| Resolution              | 520 TVL                               |
| Min. Illumination       | 0.3 Lux @ F1.2                        |
| S/N Ratio               | more than 48 dB                       |
| Electronic Shutter      | 1/50(60)sec-1/100,000sec              |
| Flickerless Mode        | ON/OFF                                |
| Lens                    | 4~9 mm manual IRIS varifocal lens     |
| Gamma Correction        | 0.45                                  |
| White Balance (AWB)     | Auto (ATW1 / ATW2 / AWC→SET / Manual) |
| Gain Control (AGC)      | High / Middle / Low(6dB~40dB)         |
| Back Light Compensation | BLC/HLC/OFF selectable                |
| Sync                    | Internal Sync                         |
| Video Output            | Composite 1.0V P-P/75Ω                |
| Power Supply            | DC12V±10%                             |
| Dimensions              | 130 Φ ×100H                           |
| Weight                  | 317                                   |
| Operating Temperature   | (-10°C~+50°C)                         |
| Certifications          | CE, FCC Certified                     |