

HC-DS30M

High Resolution Dome Camera with OSD



Main Features

- o 1/3" Sony Super HAD II CCD
- o 600 TVL High Resolution Camera
- o 0.01 lux @ F1.2
- o 3.6 mm Lens
- o AGC, AWB and BLC
- o OSD, Mirror, Privacy Masking, Motion Detection, DWDR, 2D-DNR, LSC



Feature	Specification
Image Sensor	1/3" Sony Super HAD II CCD
Pixels	PAL: 795H×596V NTSC:811H×508V
Resolution	600 TVL
Min. Illumination	0.01 lux
S/N Ratio	More than 50 dB
Electronic Shutter	1/60-1/100,000sec
Flickerless Mode	Electrical
Iris Control	Manual
Lens	3.6 mm
Gamma Correction	0.45
White Balance (AWB)	Auto
Gain Control (AGC)	Auto
Back Light Compensation	Auto
Sync	Internal Sync
Video Output	1.0Vp-P75Ωbn
Special Functions	OSD, Mirror, Privacy Masking, Motion Detection, DWDR, 2D-DNR,LSC
Power Supply	DC12V
Power Consumption	DC12V,150mA
Weight	150 gms
Operating Temperature	-10~ +50℃ RH95% Max