

DS-7204HVI-ST/L Standalone DVR



Key Features

- H.264 video compression
- Up to 4CIF resolution recording
- VGA output at 1280 × 1024 resolution
- 5 inch LCD display
- 4-ch synchronous playback
- Dual-stream
- SADP(IP Finder), NTP, DHCP, SMTP protocols



Rear Panel of DS-7204HVI-ST/L



- | | |
|------------------------|---|
| 01, Video in | 07, RS-485 interface, alarm in, alarm out |
| 02, Video out | 08, VGA interface |
| 03, Audio in | 09, RS-232 serial interface |
| 04, Line in, audio out | 10, 12 VDC power supply interface |
| 05, LAN | 11, Power switch |
| 06, USB interface | |

Specifications

DS-7204HVI-ST/L	
Video/Audio input	
Video compression	H.264
Analog video input	4-ch, BNC connector (1.0 Vp-p, 75 Ω); PAL / NTSC self-adaptive
Audio compression	G.711
Audio input	4-ch, RCA connector (2.0 Vp-p, 1 kΩ)
Video/Audio output	
VGA output	1-ch, resolution: 1280 × 1024 /60 Hz
CVBS output	2-ch, BNC connector (1.0 Vp-p,75 Ω); Resolution: PAL: 704 × 576, NTSC: 704 × 480
Audio output	1-ch, RCA connector (linear, 1 kΩ)
Recording resolution	4CIF / 2CIF / CIF
Frame rate	Main stream: 4CIF / 2CIF@12 fps, CIF@25 fps (P) / 30 fps (N) Sub stream: CIF / QCIF
Video bit rate	32 kbps ~ 2048 kbps, or user defined (max. 3072 kbps)
Stream type	Video , Video & Audio
Audio bit rate	64 kbps
Dual-stream	Support
Synchronous playback	4-ch
Voice talk input	1-ch RCA (2.0 Vp-p, 1 kΩ)
Hard disk	
SATA	1 SATA interface
Capacity	Up to 2TB capacity
External interface	
Network interface	1, RJ45 10 M / 100 M self-adaptive ethernet interface
Serial interface	1 RS-485 interface, 1 RS-232 interface
USB interface	2, USB 2.0
Alarm in	4
Alarm out	1
General	
Power supply	12 VDC
Consumption	≤ 10W (without hard disk or DVD-R/W)
Working temperature	-10 °C ~ +55 °C
Working humidity	10% ~ 90%
Chassis	Chassis for ATM DVR
Dimensions (W x D x H)	180 × 280 ×180 mm
Weight	≤5kg (without hard disk or DVD-R/W)