



Pioneers in Securities



## 6" Speed Dome 36X Outdoor S-SD4-36 / S-SD6-36 / S-SD7 36

### FEATURES

- 36x Optical Zoom, 10x Digital Zoom • Vector Drive and Micro-Stepping Technology make smooth rotation and accurate preset • Compound Movement make the speed dome reach preset in shortest route • 256 presets, horizontal turning speed reaches 250°/sec. • Continuous turning with no blind area • Perfect Solution for Day / Night Applications • High Sensitivity SONY EFFIOP Technology CCD Sensor • Adopt "Special Optical Low Pass Filter" • High Sensitivity Sensor, Excellent Picture Quality • IR Cut Filter, Auto Color & Mono Switching in low light • IP 68 with vandal proof glass • Optional Ceiling Mount

Ceiling Mount  
Stand  
Optional

Sony EFFIOP  
Technology

DIGITAL 30X  
HIGH SPEED AUTO FOCUS 36X



| Model             | S-SD4-36  | S-SD6-36 | S-SD7-36 |
|-------------------|---|----------|----------|
| Sensor            | 1/3" CCD Sony EFFIOP Technology   |          |          |
| Signal Modes      | System PAL NTSC   |          |          |
| Resolution        | 480 TVL   | 650 TVL  | 750 TVL  |
| S/N               | ≥ 60db (Enhanced)   |          |          |
| Zoom Ratio        | 36x Optical zoom, 10x digital zoom  |          |          |
| Focal Length      | 3.2 - 115.2 mm  |          |          |
| Iris              | IRIS F1.6(Wide)-F4.5(Tele)  |          |          |
| Mini Illumination | Color : 0.01 lux , B/W : 0.2 lux Color DSS : 0.001 lux , B/W DSS : 0.0004 lux   |          |          |
| Day / Night       | Auto / Day / Night  |          |          |
| Focus             | Auto / Manual / Semi-Auto   |          |          |
| Iris Adjustment   | Auto / Manual   |          |          |
| Shutter Speed     | Auto (x128 ~ 1/50 sec. ~ 1/20,000 sec.) Auto (x128 ~ 1/60 sec. ~ 1/20,000 sec.) |          |          |
| Dome Size         | 6 inch  |          |          |
| AGC               | Auto / Manual   |          |          |
| White Balance     | Auto WB /Outdoor / Indoor/One Push WB / Manual WB                               |          |          |
| BLC/HLC           | On/Off  |          |          |
| Flickerless       | On/Off  |          |          |
| Brightness        | Adjustable (0-96)   |          |          |
| Pan/Tilt          | Range Horizontal: 360 °(Endless) / Vertical: 90 °                               |          |          |
| Speed             | H4°~20°/S adjustable, V:4°~12°/S adjustable                                     |          |          |
| Preset            | 256 presets 4 pattern, 8 groups could be programmed                             |          |          |
| Patrol track      | 4 group each can record 200 actions   |          |          |
| Cruise track      | 8 Group, every group have 30 presets can join cruise                            |          |          |
| Other Scan        | 4 group support horizontal scan, frame scan, random scan                        |          |          |
| Other functions   | Auto Flip, Park Position, Power Up  |          |          |
| Communication     | RS-485  |          |          |
| Protocol          | Pelco-D, Pelco-P  |          |          |
| Input Voltage     | 24 V AC • 3 Amp.  |          |          |
| Outdoor Standard  | IP-68 Outdoor   |          |          |

Designed in Japan